

PROJECTOR LIFTS

- now you see me, now you don't.

Some considerations...

Some issues need to be taken into consideration before choosing your projector lift. As a guide to help you find the best solution for your individual use, we have listed the most common and important questions below.

How large is the projector?

To select the correct model, check the size and weight of projector before choosing your lift.

How far must the projector descent into the room?

Generally the projector's lens should be at the same height as the top of the screen's viewing area, however verify the exact position with the specification of your projector.

How much space do I have left above the ceiling?

Space will be needed for the height of lift, the projector and the closure panel, and allowance for mounting items, workspace plus ventilation.

Am I dealing with an acoustical tile or drywall ceiling?

A ceiling access door is recommended when installing in ceilings without access to the top of the lift.

Is the available space above the ceiling a plenum air return?

Housing is an optional choice and is strongly recommended since it protects the projector both from dust and theft.



Possible installation of Metro lift.



Example of Metro lift installed in acoustical tile.

Euroscreen® expands our range of Audio Video products to now also offer projector lifts. These keeps the projector hidden when it is not in use, which offers both the advantage of a sophisticated appearance and the benefit of prevention of theft and damage to the projector. The projector lifts are obtainable as motorised video projector lifts which are all design to help you mount the projector of your choice at or above the ceiling line. Additionally to projectors, the lifts can also be used to recess speakers, security cameras, video conferencing cameras etc. For full advantage of Euroscreen® concealing design concept please also learn more about Sesame™ projection screen and Commander Control System™ (www.bjurab.se).

The Metro lift

Electro mechanical lift system smoothly lower projector or other audio-visual equipment such as speakers, cameras, video conferencing equipment etc into the room for operation. The Metro lift is your choice when you want to install a lift even in a very tight space. The installation is quick and easy and the lift has a built-in adjustability which allows you to fine-tune the installation for individually conditions and needs. Metro is available in SMALL and LARGE (not in stock) and housing is optional.

- powered by strong tubular motors for simple and durable operation
- stabilising arm for operational and shake free pictures
- arm can also be used to conceal cables
- all components can be serviced from below
- easily installed between standard 5 cm ceiling joists on 40 cm centers

Dimensions & Data for Metro (nominal)	SMALL
Height of lift in closed position.....	122 cm
Maximum overall lift (W x L).....	57 x 36 cm
Ceiling opening (with closure) (W x L).....	36 x 59 cm
Optional housing (W x L).....	37 x 60 cm
Maximum projector size (W x L)*.....	21 x 46 cm
Maximum down travel.....	51 cm
Approx. travel time to lowest position.....	14 sec.
Total capacity.....	11 kg
Net weight of lift.....	9 kg
Control options (SMALL and LARGE).....	Wall switch, IR, RF or RS232 codes

* Room for cable inputs must be considered along with projector width and depth.

